

SMART DAC 600.3 FVZ LR / 600.4 VAC-P LR

NEW HAUSCHILD SPEEDMIXER* SMART DAC SERIES 250 | 400 | 600 | 700 | 800 | 1100 | 1500 | 2000







REAL-TIME TEMPERATURE CONTROL



AUTO-PROGRAMMABLE COOLING SYSTEM



SMART

SENSOR

INTEGRATION



QR CODE ENABLED

IOT COMPLIANT & REMOTE CONTROL READY

Hauschild GmbH & Co. KG

info@hauschild-speedmixer.com +49 (0)2381 48205 - 0 hauschild-speedmixer.com



THE BEAUTY OF PRECISION

Technical Data



Specification	SMART DAC600.3 FVZ LR	SMART DAC600.4 VAC-P LR
Mixing capacity (g)	Up to 600 ¹	
Mixing volume (ml)	1000 / 2000 / 2800	
Mixing Speed (rpm)	From 300 to 2200	
Display	7" color touchscreen	
Interna light	Yes	
Programs	300	
Mixing steps/program	6	
Vacuum	Νο	Yes
Minimum pressure (mbar)	N.A.	0
Vacuum pump	N.A.	External
Voltage - Frequency	230 V / 115 V - 50Hz / 60Hz	
Input Power KW	1,5	
Hight Open lid (mm)	970	
Hight - Closed lid (mm)	610	
Width (mm)	650	
Depth (mm)	620	
Weight (kg)	112	122

¹ Including material, jar, and holder when applicable.

Optional features.

- ✓ Real-Time Temperature reading
- ✓ Color Touchscreen
 ✓ Real-Time Temperature Control
 ✓ 500 programs0
 ✓ Multi and
- \checkmark Multi-program (up to 3)
- \checkmark Up to 36 mixing steps
- ✓ Up to 30 minutes mixing time
- ✓ 10" Color Touchscreen

- Sensors Integration
 - ✓ UL certification
- 🗸 IoT compatible

EXPERIENCE THE BEAUTY OF ACCURACY + ROI ENGINEERED INTO EVERY HAUSCHILD SPEEDMIXER*

Hauschild GmbH & Co. KG

info@hauschild-speedmixer.com +49 (0)2381 48205 - 0 hauschild-speedmixer.com



THE BEAUTY OF PRECISION