

SMART DAC 700.3 FVZ LR / 700.4 VAC-P LR

NEW HAUSCHILD SPEEDMIXER* SMART DAC SERIES

250 | 400 | 600 | 700 | 800 | 1100 | 1500 | 2000





REAL-TIME TEMPERATURE CONTROL



AUTO-PROGRAMMABLE COOLING





SMART SENSOR



CODE



IOT COMPLIANT & REMOTE CONTROL READY



Technical Data



Specification	SMART DAC700.3 FVZ LR	SMART DAC700.4 VAC-P LR
Mixing capacity (g)	Up to 700 ¹	
Mixing volume (ml)	1000 / 2000 / 2800	
Mixing Speed (rpm)	From 300 to 2000	
Display	7" color touchscreen	
Interna light	Yes	
Programs	300	
Mixing steps/program	6	
Vacuum	No	Yes
Minimum pressure (mbar)	N.A.	0
Vacuum pump	N.A.	External
Voltage - Frequency	230 V / 115 V - 50Hz / 60Hz	
Input Power KW	1,5	
Hight Open lid (mm)	970	
Hight - Closed lid (mm)	610	
Width (mm)	650	
Depth (mm)	620	
Weight (kg)	114	124

¹ Including material, jar, and holder when applicable.

Optional features.

- ✓ Real-Time Temperature reading
- ✓ Automatic Cooling System
 ✓ Real-Time Temperature Control
 ✓ 500 programs0

 ✓ Strobe light
 ✓ Variable counter rotation
- ✓ 500 programs0
- ✓ Multi-program (up to 3)
- ✓ Up to 36 mixing steps
- ✓ Up to 30 minutes mixing time
- √ 10" Color Touchscreen

- ✓ QR code scanner
- ✓ Sensors Integration
 - ✓ UL certification
- ✓ IoT compatible

EXPERIENCE THE BEAUTY OF ACCURACY + ROI ENGINEERED INTO EVERY HAUSCHILD SPEEDMIXER*

